

## 5. "ITE" "FREE-FLOATING" PISTON MANIFOLDS FOR R410A and (subcritical) CO<sub>2</sub> applications.

80 mm gauge SCALE options:		CLASS
BPC/410	bar/psi/°C R410A	1.6
BPC-1.0/410	bar/psi/°C R410A	1.0
BPC/410/27	bar/psi/°C R22, R407C, R410A	1.6
G-BPC/410	bar/psi/°C R410A (glycerine)	1.6
G-BC/410/127	bar/°C R22, R134a, R407C, R410A (glyc.)	1.6
G-BC/CO <sub>2</sub>	bar/°C R744 (glycerine)	1.6

### DESCRIPTION

- High density aluminium 2 valve body with hook.
- Possibility to panel mount.
- Dual O-ring seal for high pressure valve use.
- Standard delivered with 80 mm "pulse free" gauges (see page 10)
- Equipped with 4 x 1/4" MFL connection (+ schrader valve in central tee).
- Durable non slip surface, soft touch handles.

#### MB2-AP

#### 2-VALVE MANIFOLD BODY HP/LP

Hook and red and blue valve.  
 Connections : 3 x 1/4" MFL.  
 Equipped with blind nipples for easy hose storage.  
 Without gauges, hoses and carrying case.

#### 2802P-SCALE

#### MB2-AP + gauges

Add your 80 mm gauge SCALE option from the above list (example: 2802P-BPC/410).  
 Without hoses .  
 Packed in a carton.

#### 2812P-SCALE

#### MB2-AP + gauges + hoses

Add your 80 mm gauge SCALE option from the above list (example: 2812P-BPC/410).  
 2 hoses 1/4" FFL - 5/16" FFL + 1 hose 1/4" FFL, 90 cm  
 Packed in a carton

#### 2822P-SCALE

#### MB2-AP + gauges + hoses + case

Add your 80 mm gauge SCALE option from the above list (example: 2822P-BPC/410).  
 2 hoses 1/4" FFL - 5/16" FFL + 1 hose 1/4" FFL, 90 cm  
 Packed in 1 anti-shock, portable carrying case.

#### SPARE PARTS

See MANIFOLD SPARE PARTS

