

8. ALUMINIUM PISTON MANIFOLDS

80 mm gauge SCALE options:			CLASS
BC	bar/°C	R12, R22, R502	1.6
BC-1.0	bar/°C	R12, R22, R502	1.0
BPC	bar/psi/°C	R12, R22, R502	1.6
BC/4	bar/°C	R134a, R404A	1.6
BC/447	bar/°C	R134a, R404A, R407C, R507	1.6
BC-1.0/447	bar/°C	R134a, R404A, R407C, R507	1.0
BC/27	bar/°C	R22, R407C	1.6
BC/247	bar/°C	R22, R134a, R404A, R407C	1.6
G-BC	bar/°C	R12, R22, R502 (glycerine)	1.6
G-BPC	bar/psi/°C	R12, R22, R502 (glycerine)	1.6
G-BC/4	bar/°C	R134a, R404A (glycerine)	1.6
G-BC/447	bar/°C	R134a, R404A, R407C, R507 (glyc.)	1.6
G-BC/247	bar/°C	R22, R134a, R404A, R407C (glyc.)	1.6

62 mm gauge SCALE options:			CLASS
BPC	bar/psi/°C	R12, R22, R502	1.6
BC/447	bar/°C	R134a, R404A, R407C, R507	1.6
BC/247	bar/°C	R22, R134a, R404A, R407C	1.6

DESCRIPTION

- Aluminium body with tested leak proof sight glass and hook.
- Equipped with 5 x 1/4" MFL connections of which 2 have a schraeder valve (central tee + left (low) side of body). Provides additional hookups for use with e.g. vacuum gauge, adding oil, etc.
- Available with 62 mm or 80 mm "pulse free" gauges.

M2-14 **2-VALVE MANIFOLD BODY HP/LP**
 Hook and red and blue valve.
 Connections : 5 x 1/4" MFL.
 Equipped with blind nipples for easy hose storage.
 Without gauges, hoses and carrying case.

1004-SCALE **M2-14 + gauges 62 mm**
 Add your 62 mm gauge SCALE option from the above list (example: 1004-BC).
 Without hoses .
 Packed in a carton.

1084-SCALE **M2-14 + gauges 80 mm**
 Add your 80 mm gauge SCALE option from the above list (example: 1084-BC).
 Without hoses .
 Packed in a carton.

1184-SCALE **M2-14 + gauges 80 mm + hoses.**
 Add your 80 mm gauge SCALE option from the above list (example: 1184-BC).
 3 hoses 1/4" FFL, 90 cm.
 Packed in a carton.

1284-SCALE **M2-14 + gauges 80 mm + hoses.**
 Add your 80 mm gauge SCALE option from the above list (example: 1284-BC).
 3 hoses 1/4" FFL, 90 cm.
 Packed in 1 anti-shock, portable carrying case.

SPARE PARTS See MANIFOLD SPARE PARTS.

