

MV-3688 1/8" pipe thread brass **HEX LOCKNUT**
(For example used used with MV-36.. series.

MV-5501 "TEFLON" O-ring for M-series valve.

"O" RING GASKETS

- Heavy and compact "NEOPRENE" and "BUNA" composition.

MV-0077 3,97 mm int. x 7,14 mm ext. ($5/32$ "ID x $9/32$ "OD)
For thumbscrew of core depressor and MV-39.. series

MV-0099 3,97 mm int. x 8,73 mm thickness ($5/32$ "ID x $11/32$ "CS)
For Coupler of MV-5050

MV-0101 6,35 mm int. x 9,53 mm ext. x 1,59 mm thickness
($1/4$ " ID x $3/8$ " OD x $1/16$ " CS)

MV-0111 5,56 mm int. x 7,94 mm ext. x 1,59 mm thickness
($7/32$ " ID x $5/16$ " OD x $1/16$ " CS)

MV-1060 Used in MV-39.. series and core depressor couplers
4,76 mm int. x 9,53 mm ext. x 2,38 mm thickness
($3/16$ " ID x $3/8$ " OD x $3/32$ " CS) for brass "CAP"

MV-1090 7,94 mm int. x 12,7 mm ext. x 2,38 mm thickness
($5/16$ " ID x $1/2$ " OD x $3/32$ " CS)
Used in MV-39.. series and core depressor couplers.

MV-3688



MV-5501



MV-0077



MV-1060



MV-0111



MV-1090