



COILS

1. COPPER COILS (U.S. STANDARD)

ASTM B 280 and ANSI B9.1 (U.S. norms)
 "STREAMLINE" (U.S. & Canadian patented)

PART NUMBER	DIAM.	LENGTH (ft)	WALL (mm)	WEIGHT (kg/m)
INCH ANNEALING COPPER COILS				
D02050	1/8"	50	0,76	0,052
D03050	3/16"	50	0,76	0,086
D04050	1/4"	50	0,76	0,120
D05050	5/16"	50	0,81	0,200
D06050	3/8"	50	0,81	0,268
D08050	1/2"	50	0,81	0,374
D10050	5/8"	50	0,89	0,454
D12050	3/4"	50	0,89	0,456
D14050	7/8"	50	1,14	0,677
D18050	1 1/8"	50	1,21	0,975
D22050	1 3/8"	50	1,40	1,315
D26050	1 5/8"	50	1,52	1,696

2. COPPER COILS (EUR. STANDARD)

Norm EN 12735-1
 Tensile strength = soft R220

PART NUMBER	DIAM.	LENGTH (m)	WALL (mm)	WEIGHT (pc)
INCH ANNEALING COPPER COILS				
CO-04I	1/4"	15	0,80	1,86
CO-04	1/4"	15	1,00	2,25
CO-05I	5/16"	15	0,80	2,40
CO-06	3/8"	15	0,80	2,93
CO-06I	3/8"	15	1,00	3,57
CO-08	1/2"	15	0,80	3,99
CO-08I	1/2"	15	1,00	4,91
CO-10I	5/8"	15	1,00	6,24
CO-12I	3/4"	15	1,00	7,58
CO-14I	7/8"	15	1,00	8,90
METRIC ANNEALING COPPER COILS				
MCO-06	6 mm	35	1,00	4,90
MCO-08	8 mm	25	1,00	4,90
MCO-10	10 mm	25	1,00	6,30
MCO-12	12 mm	25	1,00	7,70
MCO-15	15 mm	25	1,00	9,78
MCO-18-1,00	18 mm	25	1,00	11,88
MCO-18-1,50	18 mm	25	1,50	17,30
MCO-22	22 mm	25	1,00	14,48