



90° RADIUS ELBOWS

Cat. No.	Connections		± Dimensions (mm)			
	d	a	b	z(a)	z(b)	
5090-06	06 mm	13	13	7,2	7,2	
5090-08	08 mm	12,5	12,5	5,5	5,5	
5090-10	10 mm	15	15	7	7	
5090-12	12 mm	16,5	16,5	7,5	7,5	
5090-14	14 mm	19,5	19,5	8,5	8,5	
5090-15	15 mm	22	22	11	11	
5090-16	16 mm	24	24	13	13	
5090-18	18 mm	25,5	25,5	12,5	12,5	
5090-22	22 mm	30	30	14	14	
5090-28	28 mm	36,5	36,5	17,5	17,5	
5090-35	35 mm	46	46	23	23	
5090-42	42 mm	55	55	28	28	
5090-54	54 mm	70	70	38	38	
5090-64	64 mm	83,5	83,5	51	51	
5090-76	76 mm	91,5	91,5	58	58	
5090-89	89 mm	105	105	67,5	67,5	
5090-108	108 mm	127	127	79,5	79,5	
5090-15-12	15-12 mm	22	24,5	10	12,5	
5090-18-15	18-15 mm	25	25	11	15	
5090-22-15	22-15 mm	32	33	15	21	
5090-22-18	22-18 mm	32	34	15	20	

TYPE 5090
Connections: C x C

dimensions and tolerances according to DIN EN 1254-1