

TAPES

DT-50 **LAMINATED POLYCLOTH "DUCT TAPE"** for all purposes
Temperature stability = 60°C
Tensile strength = 6,5 kg / 25 mm
48 mm width x 50 m length.

STT-796 **THREAD SEALANT TEFLON TAPE**
May be used on most thread seal connections (metal or plastic) involving air, water, sewage, chemicals, hydraulic systems and overhead sprinkles systems. Three wraps ensures a leak-free joint.
1/2" (12,7 mm) width x 6,6 m length.

STT-800 **COPPER ANTI-SEIZE TEFLON TAPE**
A clean copper based, high-temperature, anti-seize material for protection from corrosion, seizure, galling, rust carbon fusion, galvanic pitting. The copper acts like ball bearings. This tape maintains its elasticity where temperatures reach as high as 1200°C. Applications: bolts, studs, threaded fittings and couplings, valve shafts, cylinder heads, manifolds and any other connection in a hostile environment. Do not use on oxygen systems.
1/2" (12,7 mm) width x 0,11 mm thickness x 3 m length.

STT-891 **STAINLESS STEEL PIPE THREAD SEALING TAPE**
Prevents stainless steel fittings from galling or seizing during assembly and disassembly. The tape is thicker and denser than most tapes, which also ensures an effective seal up to 800 bar (12,000 psi). Do not use on oxygen systems. Will not harden or crack in the joint, No curing time, Effective within a broad range of temperatures, Non-toxic, Non-flammable, Unlimited shelf life.
1/2" (12,7 mm) width x 6,6 m length.

ATF-30 **INSULATION FOAM TAPE**
This insulation foam tape is a flexible thermal insulation which is fast and easy to install. It reduces heat loss and retards heat gain, condensation or frost.
50 mm width x 3 mm thickness x 9 m length.

ATC-30 **INSULATION CORK TAPE**
Prevents condensation strips, use on cold or hot pipes.
50 mm width x 3 mm thickness x 9 m length.

AG-2 **SEALING COMPOUND**
Seal. gum slugs - 0,9 kg.
Non hardening, water resistant, versatile and odorless. This high quality compound has excellent adhesion and may be used to seal and caulk air conditioners, refrigeration cabinets and wherever a sealing or caulking compound is needed. Available in slugs or cords.

AG-100 **SEALING COMPOUND**
Seal. gum cords 4,7 mm width x 30 m length.

