



## REDUZIERNIPPEL

Kat. Nr.	Größe d1-d2	± Maße (mm)	
		a	Z
5240-08-06	08-06 mm	15	2
5240-10-06	10-06 mm	17	3
5240-10-08	10-08 mm	17	2,5
5240-12-06	12-06 mm	19	4
5240-12-08	12-08 mm	19	3
5240-12-10	12-10 mm	20	3
5240-14-10	14-10 mm	23	4
5240-14-12	14-12 mm	22	2,5
5240-15-08	15-08 mm	23	5
5240-15-10	15-10 mm	23	4
5240-15-12	15-12 mm	23	3
5240-15-14	15-14 mm	24	2,5
5240-16-10	16-10 mm	24	5
5240-16-12	16-12 mm	25	4,5
5240-16-14	16-14 mm	25	3
5240-16-15	16-15 mm	23	1
5240-18-10	18-10 mm	26	5
5240-18-12	18-12 mm	27	5
5240-18-14	18-14 mm	27	3,5
5240-18-15	18-15 mm	27	3
5240-18-16	18-16 mm	27	3
5240-22-10	22-10 mm	32	8
5240-22-12	22-12 mm	32	7
5240-22-14	22-14 mm	33	6
5240-22-15	22-15 mm	32	5
5240-22-16	22-16 mm	32	5
5240-22-18	22-18 mm	31	3
5240-28-12	28-12 mm	39	11
5240-28-14	28-14 mm	39	9
5240-28-15	28-15 mm	39	9
5240-28-16	28-16 mm	38	8
5240-28-18	28-18 mm	38	7
5240-28-22	28-22 mm	39	5
5240-35-15	35-15 mm	46	12
5240-35-18	35-18 mm	46	10
5240-35-22	35-22 mm	47	8,5
5240-35-28	35-28 mm	47	5
5240-42-18	42-18 mm	54	14
5240-42-22	42-22 mm	56	13
5240-42-28	42-28 mm	56	10
5240-42-35	42-35 mm	56	6
5240-54-22	54-22 mm	69	21
5240-54-28	54-28 mm	69	18
5240-54-35	54-35 mm	68	13
5240-54-42	54-42 mm	70	11
5240-64-35	64-35 mm	75	15
5240-64-42	64-42 mm	77	13
5240-64-54	64-54 mm	75	10
5240-67-54	67-54 mm	85	16
5240-70-54	70-54 mm	81	11
5240-70-64	70-64 mm	82	11
5240-76-54	76-54 mm	81	11
5240-76-64	76-64 mm	77	11
5240-76-70	76-70 mm	83	11
5240-80-54	80-54 mm	81	11
5240-80-64	80-64 mm	82	11
5240-80-70	80-70 mm	83	11
5240-80-76	80-76 mm	83	11
5240-89-76	89-76 mm	83	12
5240-108-89	108-89 mm	100	15
5240-133-76	133-76 mm	110	41
5240-133-108	133-108 mm	106	23
5240-159-108	159-108 mm	130	47
5240-159-133	159-133 mm	119	49

**TYP 5240**  
 Verbindung: C x C

Abmessungen und Toleranzen gemäß DIN-1254-1