


T-STÜCK REDUZIERUNG (FORTSETZUNG)

Kat. Nr.	Größe d1-d2-d3	± Maße (mm)					
		a	b	c	z(a)	z(b)	z(c)
5130R-35-15B-28	35-15-28	32,5	30	34	9,5	19	15
5130R-35-15B-35	35-15-35	32,5	30	32,5	9,5	19	9,5
5130R-35-18B-28	35-18-28	34	32	35	11	19	16
5130R-35-18B-35	35-18-35	34	32	34	11	19	11
5130R-35-22B-28	35-22-28	36	35	37	13	19	18
5130R-35-22B-35	35-22-35	36	35	36	13	19	13
5130R-35-28B-22	35-28-22	38	38	40	15	19	24
5130R-35-28B-28	35-28-28	38	38	40	15	19	21
5130R-35-28B-35	35-28-35	38	38	38	15	19	15
5130R-35-35B-15	35-35-15	42	41	42	19	18	31
5130R-35-35B-18	35-35-18	42	41	42	19	18	29
5130R-35-35B-22	35-35-22	42	42	42,5	19	19	26,5
5130R-35-35B-28	35-35-28	42	42	42,5	19	19	23,5
5130R-35-42B-35	35-42-35	49,5	50	49,5	26,5	23	26,5
5130R-42-15B-42	42-15-42	36,5	34	36,5	9,5	23	9,5
5130R-42-18B-42	42-18-42	38	36	38	11	23	11
5130R-42-22B-35	42-22-35	40,5	39	40,5	13,5	23	17,5
5130R-42-22B-42	42-22-42	40	39	40	13	23	13
5130R-42-28B-28	42-28-28	42,5	42	43	15,5	23	24
5130R-42-28B-35	42-28-35	42,5	42	44	15,5	23	19
5130R-42-28B-42	42-28-42	43	42	43	16	23	16
5130R-42-35B-28	42-35-28	46	46	46	19	23	27
5130R-42-35B-35	42-35-35	46	46	46,5	19	23	23,5
5130R-42-35B-42	42-35-42	46,5	46	46,5	19,5	23	19,5
5130R-42-42B-22	42-42-22	50	50	49	23	23	33
5130R-42-42B-28	42-42-28	50	50	50	23	23	31
5130R-42-42B-35	42-42-35	50	50	50	23	23	27
5130R-42-54B-42	42-54-42	62	61	62	35	29	35
5130R-54-15B-54	54-15-54	41,5	40	41,5	9,5	29	9,5
5130R-54-18B-54	54-18-54	43	42	43	11	29	11
5130R-54-22B-42	54-22-42	46	45	47	14	29	20
5130R-54-22B-54	54-22-54	45	45	45	13	29	13
5130R-54-28B-42	54-28-42	49	48	49,5	17	29	22,5
5130R-54-28B-54	54-28-54	48	48	48	16	29	16
5130R-54-35B-35	54-35-35	52	52	51	20	29	28
5130R-54-35B-42	54-35-42	51	52	53	19	29	26
5130R-54-35B-54	54-35-54	51,5	52	51,5	19,5	29	19,5
5130R-54-42B-42	54-42-42	55	56	56,5	23	29	29,5
5130R-54-42B-54	54-42-54	55	56	55	23	29	23
5130R-54-54B-42	54-54-42	61	61	62	29	29	35
5130R-64-35B-64	64-35-64	58,5	64	58,5	25,5	40	25,5
5130R-64-42B-64	64-42-64	62	68	62	29	40	29
5130R-64-54B-64	64-54-64	67	70	67	34	37	34
5130R-76-35B-76	76-35-76	59,5	70	59,5	25,5	46	25,5
5130R-76-42B-76	76-42-76	63	74	63	29	46	29
5130R-76-54B-76	76-54-76	69	79	69	35	46	35
5130R-76-64B-76	76-64-76	74	79	74	40	46	40
5130R-89-35B-89	89-35-89	61,5	74,5	61,5	23,5	50,5	23,5
5130R-89-42B-89	89-42-89	68,5	82	68,5	30,5	54	30,5
5130R-89-54B-89	89-54-89	74,5	87	74,5	36,5	54	36,5
5130R-89-64B-89	89-64-89	79,5	87	79,5	41,5	54	41,5
5130R-89-76B-89	89-76-89	85,5	88	85,5	47,5	54	47,5
5130R-108-54B-108	108-54-108	85	97	85	37	64	37
5130R-108-64B-108	108-64-108	90	97	90	42	64	42
5130R-108-76B-108	108-76-108	96	98	96	48	64	48
5130R-108-89B-108	108-89-108	102,5	102	102,5	54,5	64	54,5
5130R-133-108B-133	133-108-133	139	142	139	89	94,5	89



TYP 5130R
 Verbindung: C x C x C

Abmessungen und Toleranzen gemäß DIN-1254-1