

3. COMMERCIAL - DOMESTIC THERMOSTATS

TSWM-10 PROGRAMMABLE DIGITAL THERMOSTAT
 for heat and cool installation

FEATURES

- Pre-set 7 days programs.
- Easy to change pre-set programs.
- Manual temperature override.
- Permanent temperature override.
- Time, room temperature and settings permanently showing on the display.
- Adjustable differential.
- Short cycle delay for cool mode.
- 2 batteries AA (1,5 V), not included.
- Heat and cool selectable.

SPECIFICATIONS

- Temperature range: **5°C to 30°C**.
- Differential: dip switch selectable $\pm 0,5^{\circ}\text{C}$ or $\pm 0,2^{\circ}\text{C}$.
- Temperature accuracy: $\pm 0,5^{\circ}\text{C}$.
- Rated switching power: **250 V**, 6 A resistive load or 2 A inductive load.
- Min on time in heating mode: 1 minute.
- Min off time air-conditioning mode: 3 minutes.
- Size: **130 mm x 84 mm x 30 mm**.
- **CE, GS** approved.

TSWM-30 ELECTRONIC ROOM THERMOSTAT
 for heat and cool installation

FEATURES

- Designed with highly accurate NTC thermistor sensor that, incorporated with a high performance electronic control circuit, provides accurate temperature switching control.
- Easy to operate and to install.
- Input range: **220 V AC - 250 V AC**.
- Output: Resistive load: 7 AMPS at 230 V AC Max. 1,600 W
 Inductive load: 3 AMPS at 230 V AC.
- **CE, GS** approved.

