

## 4. UNIVERSAL ECONOMY THERMOSTATS

### TSWM-35 THERMOSTAT -35°C to +35°C

#### FEATURES

- Fully encased adjustable thermostat.
- Easy to operate and to install.
- Can be used for heating or cooling applications.
- Particularly suitable for automatic adjustment of refrigeration equipment.
- Liquid filled sensing bulb (for ambient sensing).

#### SPECIFICATIONS

- Temperature range: **-35°C to +35°C**.
- Max. allowable temperature: **+60°C**.
- Accuracy: **± 3°C**.
- Differential: 1 till 3,5°C.
- Contact Resistance: Less than 50 mΩ.
- Insulation resistance: 100 mΩ.
- SPDT switch: 16 A (8 A); 250 V AC.
- Size: **86 mm x 58 mm x 35 mm**.
- CE approved.

### TSWM-35/EXT THERMOSTAT WITH CAPILLARY -35°C to +35°C

#### FEATURES

- Same as above TSWM-35 but with remote sensing bulb.
- Capillary length: 1,7 m.
- Smallest bending radius of capillary tube: 6 mm.
- Probe: copper tube (nickel plated).

### TSPM-35/EXT THERMOSTAT WITH CAPILLARY -35°C to +35°C

#### FEATURES

- Same as TSWM-35/EXT but for panel mounting.

