

# AUTOMOTIVE ACCESSORIES

## UNIVERSAL A/C FLUORESCENT DYE

**UVL-240** UNIVERSAL A/C FLUORESCENT DYE  
 240 ml (8 oz)

- Can be used in any A/C unit.
- 240 ml / 8 oz. bottle (enough for use in approx. 32 systems).
- Permanently remains in the unit, so leaks can be located anytime for repair.
- Works with any high intensity black light.
- Certified to meet SAE-J2297 for R134a and PAG oil lubricants. Compatible with R1234yf refrigerant.
- Bottle with graduated scale for correct dosage in automotive A/C systems. Use 7,5 ml (1/4 oz.) for systems containing up to 1,8 kg (4 lbs.) of refrigerant or 0,5 L (16 oz.) of oil, or 7,5 ml for every 1,8 kg of refrigerant.
- Will not harm equipment, recovery systems, A/C systems or filters
- To allow you to charge this liquid into the system, use INJEC, see below.

**INJEC** SYSTEM INJECTOR

- Used for introducing any liquid into the low side of a charged hermetic system.
- The System Injector helps prevent the venting of refrigerants into the atmosphere, as well as the introduction of air into an operating system. It can be used on sealed operating systems to avoid shutdowns.
- Entirely reusable. Constructed of rugged aluminium for long life.
- Equipped with 2 standard connections 1/4" male flare SAE with core for standard hoses and for all standard hose with depressor.
- Designed for use with any standard manifold gauge and requires no extra valves or fittings.
- Dip proof, no spill design takes the mess out of maintenance.
- **For use with Trace 2, Thawzone, Acid Neutraliser, UVL-240.**

## KIT WITH 3/8" Flare SAE Connections

**DS/O-134/6** OIL DOSOMETER with 3/8" flare female SAE  
**HDS-60-Y/V** FLEXIBLE HOSE "HEAVY DUTY" with one end 1/4" turn valve equipped with core depressor and 1 swivel end. Length: 150 cm (60")

**QVA-05** AUTOMOTIVE Low pressure service valve with U1-04M14, U1-06M14 adapters and spare gaskets  
**QVA-03** AUTOMOTIVE High pressure service valve with U1-04M14, U1-06M14 adapters and spare gaskets

**U1-04M14** ADAPTER 1/4" x M14 + O-ring  
**U1-06M14** ADAPTER 3/8" x M14 + O-ring

## KIT WITH 1/4" Flare SAE Connections

**DS/O-12** OIL DOSOMETER with 1/4" SAE female flare swivel  
**HDS-60-Y/V** FLEXIBLE HOSE "HEAVY DUTY" with one end 1/4" turn valve equipped with core depressor and 1 swivel end. Length: 150 cm (60").

**M-HDL-6** SHORT FLEXIBLE HOSE with 1/4" flare SAE with ball valve (colour coded). Length: 15 cm (6")

**K1-12** CYLINDER ADAPTER  
**QC-E3** ADAPTER (3/16" female x 1/4" male flare SAE)  
**MV-5013** R134a RETROFIT BRASS ADAPTER  
**MV-5016** R134a RETROFIT BRASS ADAPTER

**2822-BPC-AUTO** See manifolds



UVL-240



INJEC



DS/O-134/6



HDS-60Y/V

QVA-03



QVA-05



2822-BPC-AUTO