

2. "ITE" TWO VALVE DIAPHRAGM MANIFOLDS

80 mm gauge SCALE options:			CLASS
BC	bar/°C	R12, R22, R502	1.6
BC-1.0	bar/°C	R12, R22, R502	1.0
BPC	bar/psi/°C	R12, R22, R502	1.6
BC/4	bar/°C	R134a, R404A	1.6
BC/447	bar/°C	R134a, R404A, R407C, R507	1.6
BC-1.0/447	bar/°C	R134a, R404A, R407C, R507	1.0
BC/27	bar/°C	R22, R407C	1.6
BC/247	bar/°C	R22, R134a, R404A, R407C	1.6
G-BC	bar/°C	R12, R22, R502 (glycerine)	1.6
G-BPC	bar/psi/°C	R12, R22, R502 (glycerine)	1.6
G-BC/4	bar/°C	R134a, R404A (glycerine)	1.6
G-BC/447	bar/°C	R134a, R404A, R407C, R507 (glyc.)	1.6
G-BC/247	bar/°C	R22, R134a, R404A, R407C (glyc.)	1.6

R410A gauges + manifolds with special body.

DESCRIPTION

- High density black aluminium 2 valve body with tested leak proof sight glass and hook.
- Possibility to panel mount.
- Equipped with 5 x 1/4" MFL connections of which 2 have a schraeder valve (central tee + left (low) side of body). Provides additional hookups for use with e.g. vacuum gauge, adding oil, etc.
- Deep vacuum valve design: proven leak proof, easy replaceable diaphragm type valves require only fingertip pressure to close tightly and can be fully opened with only 1 turn.
- Standard delivered with 80 mm "pulse free" gauges (see page 10).
- Durable non slip surface, soft touch handles.

MB2-ADS **2-VALVE MANIFOLD BODY HP/LP**
 Hook and red and blue valve.
 Connections : 5 x 1/4" MFL.
 Equipped with blind nipples for easy hose storage.
 Without gauges, hoses and carrying case.

2802-SCALE **MB2-ADS + gauges**
 Add your 80 mm gauge SCALE option from the above list (example: 2802-BC).
 Without hoses .
 Packed in a carton.

2812-SCALE **MB2-ADS + gauges + hoses**
 Add your 80 mm gauge SCALE option from the above list (example: 2812-BC).
 3 hoses 1/4" FFL, 90 cm
 Packed in a carton

2822-SCALE **MB2-ADS + gauges + hoses + case**
 Add your 80 mm gauge SCALE option from the above list (example: 2822-BC).
 3 hoses 1/4" FFL, 90 cm
 Packed in 1 anti-shock, portable carrying case.

SPARE PARTS See MANIFOLD SPARE PARTS

