

4. "ITE" FIVE VALVE DIAPHRAGM MANIFOLDS

80 mm gauge SCALE options:			CLASS
BC	bar/°C	R12, R22, R502	1.6
BC-1.0	bar/°C	R12, R22, R502	1.0
BPC	bar/psi/°C	R12, R22, R502	1.6
BC/4	bar/°C	R134a, R404A	1.6
BC/447	bar/°C	R134a, R404A, R407C, R507	1.6
BC-1.0/447	bar/°C	R134a, R404A, R407C, R507	1.0
BC/27	bar/°C	R22, R407C	1.6
BC/247	bar/°C	R22, R134a, R404A, R407C	1.6
G-BC	bar/°C	R12, R22, R502 (glycerine)	1.6
G-BPC	bar/psi/°C	R12, R22, R502 (glycerine)	1.6
G-BC/4	bar/°C	R134a, R404A (glycerine)	1.6
G-BC/447	bar/°C	R134a, R404A, R407C, R507 (glyc.)	1.6
G-BC/247	bar/°C	R22, R134a, R404A, R407C (glyc.)	1.6

DESCRIPTION

- High density black aluminium 5 valve body with tested leak proof sight glass and hook.
- Possibility to panel mount.
- Equipped with 3 x 1/4" MFL and 1 x 3/8" MFL connections. A fifth bottom connection is plugged. Removal of this plug (1/8" NPT) allows installation of an extra service connection. 3/8" vacuum port allows 4 times faster evacuation than ordinary manifolds.
- Deep vacuum valve design: proven leak proof, easy replaceable diaphragm type valves require only fingertip pressure to close tightly and can be fully opened with only 1 turn.
- Standard delivered with 80 mm "pulse free" gauges (see page 10) and vacuum gauge (overpressure protected).
- Durable non slip surface, soft touch handles.

MB5-ADS **5-VALVE MANIFOLD BODY HP/LP**
 Hook and red, blue and 3 yellow valves.
 Connections : 3 x 1/4" MFL + 1 x 3/8" MFL
 + safety valve.
 Equipped with blind nipples for easy hose storage.
 Without gauges, hoses and carrying case.

2805-SCALE **MB5-ADS + gauges**
 827-VRP + add your 80 mm gauge SCALE option from the above list (example: 2805-BC).
 Without hoses .
 Packed in a carton.

2815-SCALE **MB5-ADS + gauges + hoses**
 827-VRP + add your 80 mm gauge SCALE option from the above list (example: 2815-BC).
 3 hoses 1/4" FFL + 1 hose 3/8" FFL, 150 cm
 Packed in a carton

2825-SCALE **MB5-ADS + gauges + hoses + case**
 827-VRP + add your 80 mm gauge SCALE option from the above list (example: 2825-BC).
 3 hoses 1/4" FFL + 1 hose 3/8" FFL, 150 cm.
 Packed in 1 anti-shock, portable carrying case.

SPARE PARTS See MANIFOLD SPARE PARTS.

