

ADJUSTABLE TORQUE WRENCH WITH OPEN END SPANNER

ATW-06-0 3/8" DRIVE ADJUSTABLE TORQUE WRENCH with open end spanner

- Spanner sizes 17 mm, 22 mm, 24 mm, 26 mm, 27 mm, 29 mm
- 3/8" drive.
- Capacity: 10 Nm to 75 Nm.

ATW-06/K4 Kit with extra spanners 19 mm, 25 mm, 28 mm & 32 mm.



MICROLOCK ADJUSTABLE & REVERSIBLE TORQUE WRENCH

ATW-2080 3/8" DRIVE ADJUSTABLE TORQUE WRENCH

- Push lock right hand/left hand.
- 3/8" drive.
- Capacity: 20 Nm to 110 Nm
- Accuracy $\pm 3\%$ of reading

SOCKETS FOR ATW-2080

- SCK-6D08M** FEMALE SOCKET: 3/8" fem. sq. x 8 mm hex fem.
- SCK-6D10M** FEMALE SOCKET: 3/8" fem. sq. x 10 mm hex fem.
- SCK-6D12M** FEMALE SOCKET: 3/8" fem. sq. x 12 mm hex fem.

ADAPTER FOR ATW-2080

- ADP-0604** ADAPTER 3/8" fem. sq. x 1/4" sq. m. drive
- ADP-0608** ADAPTER 3/8" fem. sq. x 1/2" sq. m. drive

