

UNIVERSAL BRACKETS

WBO-100	UNIVERSAL BRACKET with cross-bar, Capacity: 100 kg
WBO-100N	UNIVERSAL BRACKET without cross-bar, Capacity: 100 kg
WBO-120	UNIVERSAL BRACKET with cross-bar, Capacity: 120 kg
WBO-120N	UNIVERSAL BRACKET without cross-bar, Capacity: 120 kg
WBO-250	UNIVERSAL BRACKET with cross-bar, Capacity: 250 kg
WBO-150R	SLOPING ROOF BRACKET from 18° to 35°, Capacity: 150 kg
WBO-K10	Mounting accessories for WBO-100 and WBO-100X
WBO-K10N	Mounting accessories for WBO-100N
WBO-K12	Mounting accessories for WBO-120
WBO-K12N	Mounting accessories for WBO-120N
WBO-K15	Mounting accessories for WBO-150 and WBO-150X
WBO-K15R	Mounting accessories for WBO-150R
WBO-K25	Mounting accessories for WBO-250 and WBO-250X

FEATURES

- An elegant and practical fixing system made of pressed sheet stainless steel or pressed sheet varnished steel allowing rapid, easy and safe installation of any weight and dimension air conditioners.
- Allows wall, floor and roof installation for machines up to 250 kg and 55 cm depth.
- All the brackets are equipped with a 90° safety opening, pre-assembled with a stainless steel rivet system and complete with accessories useful for rapid and correct installation.

SPECIFICATIONS

- Stirrups: pressed sheet of 1,5 mm, 1,8 mm or 2,0 mm thick.
- Cross-bars: pressed sheet of 1,8 mm thick.
- Varnishing: RAL 1013 polyester dust for external use.
- Supplied in sets of 2, equipped with wall fixing kit and anti-vibration supports.

PART. NR.	DIMENSIONS (cm)				Material thickness (mm)
	A	B	C	D	
WBO-100	80	40	40	36	1,5
WBO-100N	80	40	40	36	1,5
WBO-250	80	50	60	55	2,0
WBO-150R	80	50	50		1,8

