Tel: +32 3 766 02 02 Fax: +32 3 766 10 67



CONDENSATE REMOVAL PUMPS for general use

WCP-010/230V WCP-020/230V CONDENSATE PUMP, max capacity 10 l/h, for air-conditioners up to 10 kW $\,$

CONDENSATE PUMP, max capacity 20 l/h, for air-conditioners up to 20 kW

FEATURES

- Reciprocating piston water-pump and separate detection-module (3 levels) up to 2 m.
- Compact and easy to conceal, suitable for residential and commercial installations.
- · Special mounting system permits fast, easy and reliable installation
- Suitable for wall mounting (splits, consoles, fan convectors) or ceiling mounting (ceiling units, double ceilings,...).

SPECIFICATIONS

• 3 detection levels: pump off (11mm ± 2

pump off $(11mm \pm 2)$ pump on $(16 mm \pm 2)$

alarm (19 mm ± 2) with relay.

- Max. suction distance: 2,5 m ± 10%.
- Max. discharge distance: 6 m ± 10% limited to a 2 m height difference.
- 230 V 50 Hz / 60 Hz 18 W or 120 V 60 Hz 24 VA.
- Alarm relay: NO NC 8 A / 250 V resistive.
- Thermal overload protection: +90°C with auto-reactivation.
- Dimensions of pump-module: 78 mm x 60 mm x 36 mm (l x d x h).
- Dimensions of detection-module: 80 mm x 38 mm x 36 mm (I x d x h).
- Supplied with DHC-06x09/1M drain hose.
- CE approved.
- · For accessories and spare parts, please consult us.

