


MANCHONS REDUCTEURS

CODE	Connexions d1-d2	Dimensions (mm)	
		a	z
5243-08-06	08-06 mm	16	10
5243-10-06	10-06 mm	18	12
5243-10-08	10-08 mm	17,5	10
5243-12-06	12-06 mm	21	15
5243-12-08	12-08 mm	20	13
5243-12-10	12-10 mm	19,5	11,5
5243-14-10	14-10 mm	22	14
5243-14-12	14-12 mm	22	13
5243-15-08	15-08 mm	24	17
5243-15-10	15-10 mm	24	16
5243-15-12	15-12 mm	24	15
5243-15-14	15-14 mm	25	14
5243-16-10	16-10 mm	25	17
5243-16-12	16-12 mm	25	16
5243-16-14	16-14 mm	26	15
5243-16-15	16-15 mm	25	14
5243-18-10	18-10 mm	27	19
5243-18-12	18-12 mm	27	18
5243-18-14	18-14 mm	29	18
5243-18-15	18-15 mm	29	18
5243-18-16	18-16 mm	28	17
5243-22-10	22-10 mm	33	25
5243-22-12	22-12 mm	33	24
5243-22-14	22-14 mm	34	23
5243-22-15	22-15 mm	34	23
5243-22-16	22-16 mm	33,5	22,5
5243-22-18	22-18 mm	35	22
5243-28-12	28-12 mm	41	32
5243-28-14	28-14 mm	42	31
5243-28-15	28-15 mm	39	28
5243-28-16	28-16 mm	40	29
5243-28-18	28-18 mm	39	26
5243-28-22	28-22 mm	42	26
5243-35-15	35-15 mm	50	38
5243-35-18	35-18 mm	47	34
5243-35-22	35-22 mm	48	32
5243-35-28	35-28 mm	49	30
5243-42-15	42-15 mm	59,5	47,5
5243-42-18	42-18 mm	57	44
5243-42-22	42-22 mm	56	40
5243-42-28	42-28 mm	56	37
5243-42-35	42-35 mm	57	34
5243-54-22	54-22 mm	68	52
5243-54-28	54-28 mm	67	48
5243-54-35	54-35 mm	68	45
5243-54-42	54-42 mm	69	42
5243-64-35	64-35 mm	71	46
5243-64-42	64-42 mm	75	46
5243-64-54	64-54 mm	75	43
5243-67-35	67-35 mm	79	56
5243-67-42	67-42 mm	88	58
5243-67-54	67-54 mm	80	48
5243-70-54	70-54 mm	77	43
5243-70-64	70-64 mm	79	44
5243-76-35	76-35 mm	88	65
5243-76-42	76-42 mm	86	59
5243-76-54	76-54 mm	82	50
5243-76-64	76-64 mm	77	44
5243-76-70	76-70 mm	80	44
5243-80-54	80-54 mm	84	50
5243-80-64	80-64 mm	79	44
5243-80-67	80-67 mm	78,5	42,5
5243-89-76	89-76 mm	84	50
5243-108-54	108-54 mm	116	84
5243-108-64	108-64 mm	110	78
5243-108-76	108-76 mm	120	86
5243-108-89	108-89 mm	100	62
5243-133-76	133-76 mm	122	89
5243-133-89	133-89 mm	108	71
5243-133-108	133-108 mm	105	58
5243-159-108	159-108 mm	159	112
5243-159-133	159-133 mm	160	125

TYPE 5243
MALE x FEMELLE



Dimensions et tolérances selon DIN EN 1254-1